




# Technical Data Sheet

## TP V SAE 5W-30 API SL/CF



### Description

Fully synthetic, all-season motor oil of API SL/CF, ACEA A5/B5 operational properties. It is based on high-quality synthetic base oil enhanced with a highly effective latest generation additive package. It prevents the formation of high/low-temperature deposits in the engine, and provides superior protection against wear. Applicable for all seasonal use. It ensures easy engine start-up and improves fuel economy.

### Specifications

API SL/CF  
ACEA A5/B5  
Ford WSS-M2C-913-A/B/C/D  
Fiat 9.55535-G1  
RN 0700

### Applications

Designed for modern high-efficiency gasoline and diesel engines of passenger cars, minivans and pickup trucks, including those equipped with a turbocharger.

### Vendor codes

1 L RX0001TPX  
4 L RX0002TPX  
20 L RX0003TPX  
60 L RX0004TPX  
208 L RX0005TPX

Properties	Method	Value
Density at 15°C, g/cm <sup>3</sup>	ASTM D4052	0,863
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	ASTM D445	12.07
Viscosity Index	ASTM D2270	153
Dynamic Viscosity CCS, at -30°C, mPa s	ASTM D5293	5950
Total Base Number, mg KOH/g	ASTM D2896	9.0
NOACK Volatility, %	ASTM D5800	9.8
Flash Point, °C	ASTM D92	210
Pour Point, °C	ASTM D97	-40

The above specifications represent average values for the particular product and are subject to modifications based on specific technical requirements.